



Reliable

Approved materials according to FDA and EC 1935/2004 regulations as well as country-specific approvals

Cost effective

Efficient cleaning of the filter during continuous operation

User friendly

Maintenance friendly through front-flush mounting

Reverse osmosis

Differential pressure measurement in reverse osmosis

The seawater is forced through a semi-permeable diaphragm under high pressure. Only pure water molecules can pass through. Salts, bacteria and viruses are retained in the filter. The resulting water is almost like distilled water. Differential pressure measurement monitors the level of contamination of the filter.

[More details](#)




VEGADIF 85

Differential pressure transmitter for measuring filter contamination

- Measurement of extremely small differential pressures through high precision measured value detection
- High reliability thanks to integrated overload diaphragm
- Multi-variable measurement via integrated sensor for measurement of static pressure

[Show Product](#)



VEGADIF 85
[Show Product](#)



Measuring range - Pressure

-40 ... 40 bar

Process temperature

-40 ... 105 °C

Process pressure

-1 ... 400 bar

Accuracy

0.065 %

Materials, wetted parts

316L
 Tantalum
 Alloy C276 (2.4819)
 Monel

Threaded connection

¼ - 18 NPT

Flange connection

≥ DN32, ≥ 1½"

Seal material

EPDM
 FKM
 Copper

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating

IP66/IP68 (0,2 bar)
 IP66/IP67
 IP66/IP68 (1 bar)