

Reliable

Reliable operation under all operating conditions

Cost effective

Maintenance-free operation of the plant

User friendly


Simple mounting and setup

Cooling tower basin

Cooling tower basin level measurement

At the bottom of the cooling tower there are nozzles for atomizing and cooling incoming hot water. As the heated water is sprayed up inside the cooling tower, it warms the air, which expands, flows upward creating updraft which pulls fresh cold air up through the slatted bottom. Draft eliminators inside the cooling tower cause the cooled water to form droplets and rain back down into the cooling tower basin. The water level in the cooling tower basin must be monitored continuously to optimise use of the circulation pumps and the cooling process.

[More details](#)



VEGAPULS C 21

Level measurement with radar in the cooling tower basin

- Simple, maintenance-free measurement
- High measurement certainty, even in extremely wet conditions, independent of pressure fluctuations
- Proven measuring principle ensures high operational reliability

[Show Product](#)

VEGAPULS C 21[Show Product](#)**Measuring range - Distance**

15 m

Process temperature

-40 ... 80 °C

Process pressure

-1 ... 3 bar

Accuracy

± 2 mm

Frequency

80 GHz

Beam angle

8°

Materials, wetted parts

PVDF

Threaded connection

G1½ / G1, 1½ NPT / 1 NPT, R1½ / R1

Seal material

FKM

Protection rating

IP66/IP68 (3 bar), Type 6P