



Reliable

Reliable measurement independent of process conditions

Cost effective

plics® concept: short delivery time and standardized operation

User friendly


Simple installation and commissioning

Evaporator

Density and pressure measurement during spice slurry thickening

In the production of spices, the spices are first mixed with water and oil to form a slurry. This is fed into an evaporator, where water is removed to turn it into a kind of syrup. The thickened spice syrup must have exactly the right density - so that it can be spread thinly onto metal sheets for oven drying, ready to be ground into powder. To ensure the optimal density of the spice syrup, it requires a continuous measurement during manufacture. The pressure in the feed pipe leading to the evaporator also requires careful monitoring to ensure a smooth-running production process.

More details



MINITRAC 31

Radiation-based sensor for density measurement in the evaporator

- External non-contact measurement through the pipeline regardless of process conditions and product properties
- Small, compact design enables space-saving installation
- PLICSCOM display and adjustment module for quick setup and on-site display of measured values

[Show Product](#)



VEGASOURCE 31

The source holder houses the radiation capsule and protects it from external influences

- Minimal space requirement and simple installation
- Pneumatic opening and closing of the source holder ensures high operational reliability
- Reliable shielding minimises the control area

[Show Product](#)



VEGABAR 82

Pressure transmitter for monitoring pressure in the evaporator feed pipe

- Wear-resistant CERTEC® ceramic measuring cell is non-sensitive to abrasion
- Absolutely front-flush ceramic diaphragm avoids sticking and abrasion damage
- Long service life thanks to the robust measuring cell

[Show Product](#)

PRO

MINITRAC 31
[Show Product](#)

Measuring range - Distance
 -

Process temperature
 -40 ... 60 °C

Process pressure
 -

Accuracy
 0.1 %

Materials, wetted parts
 No wetted material

Seal material
 no media contact

Housing material
 Aluminium
 Stainless steel (precision casting)

Protection rating
 IP66/IP67

Output
 Profibus PA
 Foundation Fieldbus
 Four-wire: 4 ... 20 mA/HART

Ambient temperature
 -40 ... 60 °C

VEGASOURCE 31
[Show Product](#)

Ambient temperature
 -20 ... 80 °C

PRO

VEGABAR 82
[Show Product](#)

Measuring range - Distance
 -

Measuring range - Pressure
 -1 ... 100 bar

Process temperature
 -40 ... 150 °C

Process pressure
 -1 ... 100 bar

Accuracy
 0.05 %

Materials, wetted parts
 PVDF
 316L
 Alloy C22 (2.4602)
 PP
 1.4057
 1.4410
 Alloy C276 (2.4819)
 Duplex (1.4462)
 Titanium Grade 2 (3.7035)

Threaded connection
 $\geq G\frac{1}{2}$, $\geq \frac{1}{2}$ NPT

Flange connection
 $\geq DN15$, $\geq \frac{1}{2}$ "

Hygienic fittings
 Clamp ≥ 1 " - DIN32676, ISO2852
 Slotted nut $\geq DN25$ - DIN 11851
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 DRD connection \varnothing 65 mm
 SMS 1145 DN51
 SMS DN38
 Swagelok VCR screwing
 Varivent G125
 Varivent N50-40
 for NEUMO BioControl D50 PN16 / 316L

Seal material
 EPDM
 FKM
 FFKM