



Reliable

Reliable buildup measurement despite high temperatures

Cost effective

Monitoring the formation of buildup ensures high availability of the cyclone

User friendly

Simple external mounting

Cyclone

Buildup measurement in cyclones

In clinker production, cyclones are used to preheat the raw meal. Before the raw meal enters the rotary kiln it is preheated to +900 °C in the cyclone. Constant monitoring of the buildup thickness on the walls ensures a continuous process.

[More details](#)



SOLITRAC 31

Radiometric measurement of buildup in cyclones

- Exact measuring results, independent of process conditions
- High process reliability through buildup detection
- High plant availability thanks to non-contact measurement

[Show Product](#)



VEGASOURCE 31

Container for radioactive source capsules

- High operational safety ensured through pneumatic opening and closing of source holder
- Comprehensive shielding reduces size of controlled areas
- Minimal space requirements and simple mounting

[Show Product](#)

SOLITRAC 31
[Show Product](#)


Measuring range - Distance
3 m

Process temperature
-

Process pressure
-

Accuracy
± 0.5 %

Materials, wetted parts
No wetted material

Seal material
no media contact

Housing material
Aluminium
Stainless steel (precision casting)

Protection rating
IP66/IP67

Output
Profibus PA
Foundation Fieldbus
Four-wire: 4 ... 20 mA/HART

Ambient temperature
-40 ... 60 °C

VEGASOURCE 31
[Show Product](#)


Ambient temperature
-20 ... 80 °C