



Reliable

Reliable measurement despite steam and changing stock temperatures and densities

Cost effective

Optimal utilization of the container volume

User friendly

Simple installation and setup

Storage towers

Level measurement in storage towers

Large quantities of prepared stock are needed to keep a paper mill running continuously. This material is stored in high storage towers. They are characterised by their large material throughput and agitators that ensure the homogeneity of the stock. Inside, the warm stock generates lots of steam and the pumping and stirring processes make the surface very turbulent. Reliable level measurement ensures a continuous supply of stock and prevents the agitator from running dry.

[More details](#)



VEGABAR 82

Hydrostatic level measurement as dry run protection for the agitator

- Front-flush installation in ball valve fitting
- Installation and removal without emptying storage tower
- Long-term stability thanks to dry measuring cell

[Show Product](#)



VEGAPULS 6X

Level measurement with radar in storage towers

- Non-contact, maintenance-free level measurement
- Reliable measurement, unaffected by steam
- Very good beam focusing enables exact measurement, even with heavy deposits on the silo walls

[Show Product](#)

PRO

VEGABAR 82
[Show Product](#)

Measuring range - Distance

-

Measuring range - Pressure

-1 ... 100 bar

Process temperature

-40 ... 150 °C

Process pressure

-1 ... 100 bar

Accuracy

0.05 %

Materials, wetted parts

PVDF
 316L
 Alloy C22 (2.4602)
 PP
 1.4057
 1.4410
 Alloy C276 (2.4819)
 Duplex (1.4462)
 Titanium Grade 2 (3.7035)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN15, ≥ ½"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ DN25 - DIN 11851
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 DRD connection ø 65 mm
 SMS 1145 DN51
 SMS DN38
 Swagelok VCR screwing
 Varivent G125
 Varivent N50-40
 for NEUMO BioControl D50 PN16 / 316L

Seal material

EPDM
 FKM
 FFKM

PRO

VEGAPULS 6X
[Show Product](#)

Measuring range - Distance

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz
 26 GHz
 80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE
 PVDF
 316L
 PP
 PEEK

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygienic fittings

Clamp ≥ 1½" - DIN32676, ISO2852
 Slotted nut ≥ 2", DN50 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienic screw connections ≥ DN50 tube ø53 -
 DIN11864-1-A
 Hygienic flange connection ≥ DN50 DIN11864-2
 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
 3-A
 DRD connection ø 65 mm
 SMS 1145 DN51